



PORTABLE PRINTERS



SOL58



* With Paper & Label Printing

SOL80/80L



* With Paper & Label Printing

FEATURES

- Support 1D, 2D bar code printing
While compatible with Windows, Linux, Android and IOS systems
- Super battery life with smart power saving and power consumption control functions, to ensure longer printing time
- Support USB, COM, Bluetooth & Wi-Fi communications
- Supports sound and light reminder when out of paper & abnormal printing
- Drop Resistant on concrete floor from 1.5m

SPECIFICATIONS:

Print parameter	Printing Method	Thermal Line	
	Printing Width	48mm	72mm
	Resolution	384 dots/line (8dots/mm, 203dpi)	
	Printing Speed	70mm/sec	90mm/sec
	Interface	USB+ Bluetooth	
	Line spacing	3.75mm (Can adjust line spacing by command)	
	Line No.	Font A:32 character /Line	Font A:48 character /Line
		Font B:42 character/Line. Simple, traditional Chinese-16 lines	Font B:64 character/Line. Simple, traditional Chinese-24 lines
	Character	The standard GB18030 simplified / traditional Chinese characters library	
	Character Size	ANK character, Font A : 1.5×3.0mm (12×24点) Font B : 1.1×2.1mm (9×17点) Simplified/Traditional : 3.0×3.0mm (24×24点)	
Bar code character	Extended character set	PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/Greek/Hebrew/EastEurope/Iran/WPC1252/PC866/PC852/PC858/Iran/I/Latvian/Arabic/PT151, 1251/PC737/WPC/1257/Thai/Vietnam/PC864/ PC1001/(Latvian)/(PC1001)/(PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)	
	Bar code	1D.Bar code : UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/ CODABAR/CODE93/CODE128 . 2D.Bar code : QR CODE	
	Graphics printing	Supports bitmap download and print	
Power saving Mode	Smart power saving	Yes	
	Variable speed printing	Yes	
Detection	Sensor	No Paper Detection	
Indicator	Power Display	Yes	
	Charge Indicator	Yes	
	Lack of paper	Yes	
	Beep	No Paper, Abnormal Printing	
Paper	Type	Thermal	
	Width	57.5±0.5mm	79.5±0.5mm
	Thickness	≤ 0.12mm	
	Diameter	≤ 40mm	
	Feed	Easy (Clamshell feed)	
Print Command	Commands	ESC/POS	
Power	Type	Rechargeable Lithium polymer battery	
	Capacity	2000mAh/7.4V	2400mAh/7.4V
	Charger	9.0V/2A	
Buffer	Input	4KB	
	NV Flash	40KB	
Physical features	Weight	200G	
	Box Dimension	114*80*50(MM)	
Environment	Operating	Temp : 5~45℃ , Humidity : 10~80%	
	Storage	Temp : -10~50℃ , Humidity : 10~90% (No Dew)	
Reliability	Print head life	50KM (Printing Density≤12.5)	
Software	Driver	Android,IOS,Linux,Win2000,Win2003,WinXP,Win7,Win8,Win8.1, Win 10	



PoS Tektronics Limited

Rooms 1318-19, 13 / F, Hollywood Plaza,
610 Nathan Road, Mongkok, Kowloon, Hong Kong
Email: pcpos@yahoo.com
Web: www.postektronics.com

